

SAFETY DATA SHEET

ENERGIZE

SECTION 1 – CHEMICAL PRODUCT & COMPANY IDENTIFICATION

PRODUCT IDENTIFIER: ENERGIZE
 PRODUCT USE: Mechanical Warewash Detergent
 VENDOR NAME AND ADDRESS: Alpine Specialty Chemicals Ltd.
 9 City View Drive, Etobicoke, Ontario M9W 5A5
 24 HOUR EMERGENCY NO. 613-996-6666 (CANUTEC)

SECTION 2 – HAZARDS IDENTIFICATION

CLASSIFICATION

- SKIN CORROSION/IRRITATION- CATEGORY 1A; EYE DAMAGE/IRRITATION –CATEGORY 1

LABEL ELEMENTS



- SIGNAL WORD: DANGER
- HAZARD STATEMENT(S): CAUSES SEVERE SKIN BURNS AND EYE DAMAGE
- PRECAUTIONARY STATEMENTS: Wash skin thoroughly after handling. Wear chemical safety glasses and nitrile gloves. Do not mix with acids. Dispose of contents/ containers in accordance with local regulations.
- RESPONSE: - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

IF ON SKIN: Wash with plenty of water. Get medical attention. Take off contaminated clothes and wash it before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF SWALLOWED: Immediately call a poison center or doctor. Rinse mouth.

SECTION 3 – COMPOSITION / INFORMATION INGREDIENTS

CHEMICAL NAME	%	CAS.NO
Sodium Hydroxide	30-60	1310-73-2
Nitritolactic acid trisodium salt	5-15	139-13-9

SECTION 4 – FIRST AID MEASURES

Inhalation: Remove source of exposure or move to fresh air. Call a poison centre or doctor if you feel unwell.

Skin Contact: Take off immediately all contaminated clothing. Rinse skin with water or shower. Get medical attention or advise. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention or advice.

SAFETY DATA SHEET

ENERGIZE

Ingestion: Immediately call a Poison Centre or doctor. Do not induce vomiting.

Note to physician: Treat symptomatically, no specific antidote. See toxicological information (section 11)

SECTION 5 – FIRE FIGHTING MEASURES

Extinguishing Media:

Suitable Extinguishing Media: Use water spray, fog or foam.

Unsuitable Extinguishing Media: None known

Specific hazards arising from the product: No specific fire or explosion hazard.

Hazardous thermal decomposition products: Decomposition products may include the following materials: carbon dioxide, carbon monoxide and nitrogen oxides.

Advice for fire-fighters: Not available.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:

Wear suitable protective clothing. Wear eye/face protection.

Environmental precautions: Do not allow to enter drains, sewers or watercourses. Advise Authorities if spillage has entered water course or sewer or has contaminated soil or vegetation.

Methods and materials for containment and cleaning up: Caution - spillages may be slippery. Avoid generation of dust. Sweep or preferably vacuum up and collect in suitable containers for recovery or disposal.

Reference to other sections See also Section 8.

SECTION 7 – HANDLING AND STORAGE

Precautions for safe handling: Ventilate adequately, otherwise wear an appropriate breathing apparatus. Avoid contact with eyes, skin or clothing. Wash thoroughly after handling.

Storage Procedures: Keep containers closed when not in use. Store between the following temperatures: -10 to 40°C.

SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

CHEMICAL NAME	ACGIH TLV		OSHA PEL		AIHA WEEL	
	TWA	STEL	TWA	Ceiling	8 hour TWA	Short term TWA ☉
Sodium Hydroxide	2 mg/m ³		2 mg/m ³		2 mg/m ³	
Nitroliacetic acid trisodium salt	Not available		Not available		Not available	

ACGIH= American Conference of Governmental Industrial Hygienists. TLV = Threshold Limit Value. TWA = Time-weighted Average. STEL = Short-term Exposure Limit OSHA = US Occupational Safety and Health Administration. PEL = Permissible Exposure Limits. AIHA = AIHA Guideline Foundation. WEEL = Workplace Environmental Exposure Limit.

Appropriate Engineering Control: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual Protection Measure:

Eye/Face Protection: Do not get into eyes. Wear chemical safety goggles.

Skin Protection: Prevent all skin contact, wear nitrile gloves.

Respiratory protection: Not required

SAFETY DATA SHEET

ENERGIZE

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Cast solid, white color.
Odour:	Odourless
pH :	13 (1 %)
Melting Point:	Not available
Boiling point:	Not available
Flash Point:	Not available
Evaporation Rate:	Not available
Flammability:	Not available
Explosive Limit:	Not available
Relative Density:	Approx. = 1.68 (Water = 1)
Viscosity:	Not available
Solubility in water:	Soluble
Auto ignition temperature	Not available

SECTION 10 – STABILITY AND REACTIVITY

STABILITY:	Stable
INCOMPATIBILITY:	Acids
HAZARDOUS DECOMPOSITION PRODUCTS:	None
HAZARDOUS POLYMERIZATION:	Will not occur.
CONDITIONS TO AVOID:	Contact with acids will generate heat.

SECTION 11 – TOXICOLOGICAL INFORMATION

Chemical Name	LC50	LD50	LD50 (dermal)
Sodium Hydroxide	121 mg/l (fish)	Not Available	1350 mg/kg (Rabbit)
Nitilotiacetic acid trisodium salt	Not Available	>5000 mg/kg (rat)	>5000 mg/kg (rat)

Routes of exposure: Skin contact, Eye contact, Ingestion.

Eye contact: Material will cause chemical burns. May cause permanent damage if eye is not immediately irrigated.

Skin contact. Material will cause chemical burns.

Inhalation: Material will cause coughing and respiratory tract irritation.

Acute toxicity:

Eye contact: Causes serious eye damage.

Skin contact: Causes severe skin burns

Inhalation: Causes respiratory irritation.

Ingestion: Causes burns to mouth, throat and stomach.

SAFETY DATA SHEET

ENERGIZE

Reproductive toxicity: No evidence of reproductive toxicity or developmental toxicity.

STOT - single exposure irritating to respiratory system.

STOT - Not classified.

Aspiration hazard: Not classified.

SECTION 12 – ECOLOGICAL CONSIDERATION

Toxicity Fish: (Brachydanio rerio) LC50 (96 hour) 210 mg/l Aquatic invertebrates: (Daphnia magna) EC50 (48 hour) 1700 mg/l.

Persistence and degradability Inorganic: Soluble silicates, upon dilution, rapidly depolymerize into molecular species indistinguishable from natural dissolved silica.

Bio accumulative potential Inorganic: The substance has no potential for bioaccumulation.

Mobility in soil: Not applicable.

Other adverse effects: The alkalinity of this material will have a local effect on ecosystems sensitive to changes in pH.

SECTION 13 – DISPOSAL CONSIDERATIONS

Waste Disposal: In accordance with federal, provincial or local government requirements.

SECTION 14 – TRANSPORT INFORMATION

TDG Classification: UN 3262 Corrosive Solid, Basic, Inorganic N.O.S. (Sodium Hydroxide)
Class 8 Packing Group III

SECTION 15 – REGULATORY INFORMATION

Refer to section 2.

SECTION 16 – OTHER INFORMATION

EFFECTIVE DATE: February 12, 2016: **Revision 1**

Prepared by: Lab Personnel

Phone: (416) 744-2120

Website: www.alpinechem.com

Disclaimer:

The information contained in this form is based on data from sources considered technically reliable and has been provided in good faith in accordance with the available material. It is provided as a service to the persons using the product but conditions of use and handling may involve other and additional consideration beyond our control. No warranty, expressed or implied, is made and we will not be liable for any damages, losses, injuries or consequential damages which may result from the use or reliance on any information in this form.